



## Made in the USA

THE LURE OF THE GREAT OUTDOORS...

TROLLING THE LAKE FOR THE PRIZE-WINNING BASS, DRIVING GROSS COUNTRY FOR THE ANNUAL RV RALLY, HAULING YOUR GEAR FOR A WEEKEND OF CAMPING OR SAILING THE OCEAN ON A BREEZY SUMMER'S DAY... WHATEVER YOUR PASSION NOTHING BRINGS YOU CLOSER TO THE GREAT OUTDOORS THAN ENJOYING IT FROM YOUR FAVORITE BOAT OR RV. TO ENSURE A DAY OF FUN IN THE SUN, RELIABLE BATTERIES ARE THE HEART TO POWERING YOUR BOATING AND RV ACTIVITIES.

SINCE 1925, TROJAN BATTERY HAS ENGINEERED THE WORLD'S MOST RELIABLE, LONG-LASTING, DEEP-CYCLE BATTERIES SPECIFICALLY DESIGNED TO MEET THE DEMANDS OF THE AVID RV'ER AND RECREATIONAL BOATER. TROJAN OFFERS THE BROADEST PORTFOLIO OF RECREATIONAL BATTERIES TO MEET YOUR SPECIFIC HOUSE POWER AND STARTING APPLICATIONS. RANGING FROM OUR DEEP-CYCLE FLOODED SERIES TO OUR MAINTENANCE-FREE AGM AND GEL BATTERIES THERE'S NO BETTER POWER SOLUTION THAN THE PROVEN TECHNOLOGY OF TROJAN. WHEREVER THE ROAD OR WATER MAY TAKE YOU, TROJAN BATTERIES WILL BE ALONG FOR THE RIDE TO POWER YOUR MARINE AND RV ADVENTURES.

# **Deep-Cycle Flooded Batteries...** Rugged Durability and Long Life

Trojan's deep-cycle flooded batteries are the flagship of Trojan's product portfolio. Engineered to provide rugged durability, outstanding performance and long life, Trojan's deep-cycle flooded batteries are perfectly suited for use in a variety of recreational applications. An all-around power house, the deep-cycle flooded batteries feature Trojan's historically-proven engineering with T2 Technology™, an advanced battery technology for maximum sustained performance, longer life and increased total energy.



### Alpha Plus<sup>®</sup> Paste with T2 Technology<sup>™</sup>

#### Maximum Operating Performance

Trojan's Alpha Plus Paste is a proprietary, high density paste formulation engineered to deliver outstanding battery performance. It optimizes porosity development in the active material utilizing the active material more effectively resulting in sustained battery performance over a longer period of time. Trojan's T2 Technology introduces a patent-pending T2 metal agent into Alpha Plus Paste strengthening its electrochemical processing capabilities. Alpha Plus Paste with T2 Technology increase both sustained capacity and total overall ampere-hours resulting in more operating power. It's a key reason why Trojan batteries consistently outperform the competition.

### Trojan Grid Technology

Reduced Downtime

Trojan's grid technology is a lead antimony alloy grid mixture formulated specifically for use with Trojan's Alpha Plus Paste with T2 Technology. The grid formulation provides exceptional structural adhesion between the Alpha Plus Paste and the grid frame. Thick grids reinforce the strength of the frame and reduce overall corrosion. The grid configuration is optimized to enhance current flow through the grid network providing exceptional battery performance, reducing downtime and lowering overall maintenance costs.

### Maxguard<sup>®</sup> T2 Separator

Longer Battery Life

Exclusively available in Trojan batteries is our Maxguard T2 advanced separator. Its multi-rib geometry design keeps acid channels open longer enhancing electrochemical processing while reducing the risk of stratification. Maxguard's proprietary rubber-based material formulation inhibits antimony transfer between the positive grids and negative plates; a protection not available in many other competitor batteries. A newly fortified, thick back web provides even greater separator strength resulting in a more robust battery with increased protection against failures caused by separator degradation. Trojan's Maxguard T2 advanced separator sustains performance, provides longer battery life and significantly lowers operating costs.



THE MAXGUARD<sup>®</sup> T<sub>2</sub> SEPARATOR DIFFERENCE

## Sealed Maintenance-Free Batteries... Outstanding Performance and Reliability

For outdoor recreational vehicles and marine applications sealed, maintenance-free batteries offer a convenient power solution for RV and boating applications. Trojan offers a full line of sealed, maintenance-free, deep-cycle AGM and gel products engineered for optimum performance and longevity delivering more hours to explore the great outdoors.

## **Deep-Cycle Gel Batteries**

Trojan deep-cycle gel batteries are sealed, maintenance-free batteries that deliver superior power in demanding RV and marine applications. Engineered for rugged durability, outstanding performance and long battery life, Trojan's deep-cycle gel batteries feature a number of important design characteristics that provide significant advantages over competing gel products. The gelled electrolyte is a proprietary formulation containing sulfuric acid, fumed silica, pure demineralized, deionized water and a phosphoric acid additive. This exclusive formulation produces a homogenous gel that delivers consistent performance and reliability. The heavy duty thick grids lock active material onto the grid network to efficiently deliver more concentrated energy to the terminals. Premium grade, double-insulated separators allow maximum charge flow between the plates for optimum performance. Because gel batteries can operate in a variety of extreme temperatures , they are ideal for use in a wide range of environments.



## **Deep-Cycle AGM Batteries**

Trojan's deep-cycle absorbed glass mat (AGM) sealed, maintenance-free batteries feature a number of design elements to provide optimum performance. Robust plates extend the life cycle of Trojan's deep-cycle AGM batteries. A separator of glass fibers serves to isolate the positive and negative plates while acting as a blotter to absorb the electrolyte. The separator is maintained under compression between plates to assure contact with plate surfaces. A computer-generated grid design is optimized for high-power density. Low calcium grid alloy reduces gas emissions and a flame arresting, one-way pressure relief vent prevents buildup of excessive pressure. Trojan's deep-cycle AGM batteries are low-temperature tolerant, shock and vibration resistant and have a low internal resistance for higher discharge current and higher charging efficiency. Designed with advanced battery technology, Trojan AGM batteries deliver dependable power with long battery life.



### **OverDrive AGM 31™** Deep-Cycle Endurance

The Trojan OverDrive AGM 31 battery is a true deep-cycle AGM battery. Engineered exclusively to withstand the rigors and abuse of deep discharge applications, the OverDrive incorporates a series of design features essential to deliver energy storage and duration required for when your boat or RV goes through long periods of time without power hook ups. Selecting the wrong type of battery will cause disappointing performance of boat and RV house power functions such as lighting, water pump, furnace and other appliances. The Trojan OverDrive AGM 31 delivers high power cycling for extended periods of time and is designed to work hard so you can play hard in the great outdoors.



## **TransPower™ ST1000 AGM 31** Starting Battery

The TransPower ST1000 is built specifically for demanding starting applications and is designed with unique features that provide extended battery life when compared to conventional starting batteries. As a sealed, maintenance-free AGM 31 starting battery, the Trojan TransPower ST1000 is engineered for rugged durability, outstanding cranking power and provides nearly double the battery life of a flooded starting battery. Design features that contribute to the overall performance and durability of the TransPower ST1000 include an advanced paste formulation, heavy-duty plate design and rugged polypropylene case. The TransPower ST1000 is durable enough to withstand the rigorous abuse recreation vehicle and marine applications can cause.



*Clean energy for life*<sub>™</sub>

# **Product Specification Guide**

BCI	ТҮРЕ	CAPACITY <sup>A</sup> Minutes		CRANKING Performance		CAPACITY <sup>B</sup> Amp-Hours (AH)				ENERGY (kWh)	TERMINAL	DIME	NSIONS <sup>C</sup> Inches	WEIGHT Ibs.	HydroLink™ or	
GROUP SIZE		@25 Amps	@75 Amps	C.C.A. <sup>D</sup> @0°F	C.A. <sup>E</sup> @32°F	5-Hr Rate	10-Hr Rate	20-Hr Rate	100-Hr Rate	100-Hr Rate	Type <sup>G</sup>	Length	Width	Height <sup>F</sup>	(kg)	Single-Point Watering Kit <sup>#</sup>
			6 \	OLT	DEEP	-CYC	LE FL	.00D	ED B	ATTER	ES - wi	th T2 TEO	CHNOLO	GY™		
GC2	T-105	447	115	-	-	185	207	225	250	1.50	1, 2, 3, 4	10.30 (262)	7.11 (181)	11.07 (281)	62 (28)	HydroLink
GC2	T-105 Plus	447	115	-	-	185	207	225	250	1.50	1, 2, 3,	10.30 (262)	7.11 (181)	11.07 (281)	62 (28)	Single-Point
GC2	T-125	488	132	-	-	195	221	240	266	1.60	1, 2, 3, 4	10.30 (262)	7.11 (181)	11.07 (281)	66 (30)	HydroLink
GC2	T-125 Plus	488	132	-	-	195	221	240	266	1.60	1, 2, 3	10.30 (262)	7.11 (181)	11.07 (281)	66 (30)	Single-Point
GC2H	T-145	530	145	-	-	215	239	260	287	1.72	1, 2, 3, 4	10.30 (262)	7.11 (181)	11.90 (302)	72 (33)	HydroLink
GC2H	T-145 Plus	530	145	-	-	215	239	260	287	1.72	1, 2, 3	10.30 (262)	7.11 (181)	11.90 (302)	72 (33)	Single-Point
902	J305H-AC*	781	215	-	-	295	331	360	400	2.40	6	11.66 (296)	6.94 (176)	14.42 (366)	98 (45)	Single-Point
903	L16H-AC*	935	245	-	-	357	400	435	483	2.89	6	11.66 (296)	6.94 (176)	16.74 (425)	125 (57)	Single-Point
	12 VOLT DEEP-CYCLE FLOODED BATTERIES - with T2 TECHNOLOGY™															
24	24TMX	140	36	-	-	70	78	85	94	1.13	5, 7, 8, 9	10.92 (277)	6.62 (168)	9.25 (235)	47 (21)	N/A
27	27TMX	175	45	-	-	85	97	105	117	1.40	5, 9	12.72 (323)	6.60 (168)	9.24 (235)	55 (25)	N/A
921	J185H-AC*	440	121	-	-	185	207	225	249	2.99	6	14.97 (380)	6.91 (176)	14.71 (374)	123 (56)	Single-Point
24	SCS150	150	36	530	650	80	92	100	111	1.33	10	11.30 (286)	6.73 (171)	9.80 (248)	50 (23)	N/A
27	SCS200	200	52	620	760	95	105	115	128	1.54	10	12.80 (324)	6.73 (171)	9.80 (248)	60 (27)	N/A
30H	SCS225	225	57	665	820	105	118	130	144	1.73	10	13.92 (354)	6.75 (171)	9.95 (253)	66 (30)	N/A

# **HydroLink™** Battery Watering Made Easy

Proper maintenance and periodic watering are important factors in maximizing the performance and life of Trojan deepcycle flooded batteries. Battery maintenance can be a costly, time-consuming and messy job. With Trojan's HydroLink<sup>™</sup> advanced, single-point watering system, precise battery watering is made easy saving valuable time and money.

Trojan's HydroLink watering system is specifically designed to work with Trojan 6-volt and 12-volt flooded batteries\*\* and takes the guess work out of properly watering flooded batteries. The unique HydroLink<sup>™</sup> vent assembly features an independent water level indicator, valve shut off and dual flame arrestors. With a simple installation of the HydroLink manifolds and tubing, the system is ready for use. Once installed, a complete set of batteries can be filled in less than 30 seconds. The HydroLink<sup>™</sup> watering system comes with a four-year, limited warranty.





\*\* HydroLink is not compatible with all batteries. See warranty for details: www.trojanbattery.com/products/hydrolink-watering-system/

# **Product Specification Guide**

BCI GROUP SIZE	ТҮРЕ	CAPACITY <sup>A</sup> Minutes		CRANKING Performance		CAPACITY <sup>B</sup> Amp-Hours (AH)				ENERGY (kWh)	TERMINAL	DIMENSIONS <sup>c</sup> Inches (mm)			WEIGHT lbs.	HydroLink™ or
		@25 Amps	@75 Amps	C.C.A. <sup>D</sup> @0°F	C.A. <sup>E</sup> @32°F	5-Hr Rate	10-Hr Rate	20-Hr Rate	100-Hr Rate	100-Hr Rate	Type <sup>G</sup>	Length	Width	Height <sup>F</sup>	(kg)	Single-Point Watering Kit <sup>H</sup>
	12 VOLT DEEP-CYCLE AGM BATTERIES															
24	24-AGM	137	-	500	600	67	70	76	84	1.01	6	10.77 (274)	6.84 (174)	8.62 (219)	54 (24)	N/A
27	27-AGM	158	-	550	660	77	82	89	99	1.19	6	12.05 (306)	6.84 (174)	9.32 (237)	64 (29)	N/A
31	31-AGM	177	-	600	720	82	92	100	111	1.33	6	13.73 (349)	6.80 (173)	9.16 (233)	69 (31)	N/A
31	OverDrive AGM 31™	180	-	730	875	84	93	102	112	1.34	11	13.42 (341)	6.81 (173)	9.21 (234)	69 (31)	N/A
	STARTING AGM BATTERY															
31	TransPower™ ST1000 AGM 31	200	-	1000	1200	88	93	102	105	1.26	11	13.42 (341)	6.81 (174)	9.21 (234)	75 (34)	N/A
	DUAL PURPOSE AGM BATTERIES															
GC2	6V-AGM	385	-	1100	1400	154	184	200	221	1.33	6	10.28 (261)	7.08 (180)	10.74 (273)	65 (29)	N/A
8D	8D-AGM	460	-	1450	1850	179	210	230	254	3.05	6	20.47 (520)	10.64 (270)	9.08 (231)	167 (76)	N/A

BCI GROUP SIZE	ТҮРЕ	CAPACITY <sup>A</sup> Minutes		CRANKING Performance		CAPACITY <sup>B</sup> Amp-Hours (AH)				ENERGY (kWh)	TERMINAL	DIMENSIONS <sup>c</sup> Inches (mm)			WEIGHT lbs.	HydroLink™ or
		@25 Amps	@75 Amps	C.C.A. <sup>D</sup> @0°F	C.A. <sup>E</sup> @32°F	5-Hr Rate	10-Hr Rate	20-Hr Rate	100-Hr Rate	100-Hr Rate	Type <sup>6</sup>	Length	Width	Height <sup>F</sup>	(kg)	Single-Point Watering Kit <sup>H</sup>
DEEP-CYCLE GEL BATTERIES																
GC2	6V-GEL	394	-	575	825	154	167	189	198	1.19	6	10.25 (260)	7.08 (180)	10.82 (275)	68 (31)	N/A
24	24-GEL	147	-	330	460	66	72	77	85	1.02	6	10.92 (277)	6.61 (168)	9.26 (235)	52 (24)	N/A
27	27-GEL	179	-	395	545	76	84	91	100	1.20	7	12.73 (323)	6.38 (162)	9.26 (235)	62 (28)	N/A
31	31-GEL	200	-	445	620	85	94	102	108	1.30	7	12.94 (329)	6.82 (173)	9.64 (245)	70 (32)	N/A



A. The number of minutes a battery can deliver when discharged at a constant rate at 80°F (27°C) and maintain a voltage above 1.75 V/cell. Capacities are based on peak performance.
 B. The amount of amp-hours (AH) a battery can deliver when discharged at a constant rate at 80°F (27°C) for the 20-Hour and 86°F (30°C) for the 5-Hour rate and maintain a voltage above 1.75 V/cell. Capacities are based on peak performance.
 Dimensions are based on nominal size. Dimensions may vary depending on type of handle or terminal. Batteries to be mounted with *5* inches (12.7mm) spacing minimum.
 D. C.A. (Cold Granking Amps) - the discharge load in amperes which a new, fully charged battery can maintain for 30 seconds at 0°F at a voltage above 1.2 V/cell.
 C.A. (Cold Granking Amps) - the discharge load in amperes which a new, fully charged battery can maintain for 30 seconds at 32°F at a voltage above 1.2 V/cell.
 C.A. (Cold Granking Amps) - the discharge load in amperes which a new, fully charged battery can maintain for 30 seconds at 32°F at a voltage above 1.2 V/cell.
 C.A. (Cond Granking Amps) - the discharge load in amperes which a new, fully charged battery can maintain for 30 seconds at 32°F at a voltage above 1.2 V/cell.
 C.A. (Cond Granking Amps) - the discharge load in amperes which a new, fully charged battery can waintain for 30 seconds at 32°F at a voltage above 1.2 V/cell.
 T. Dimensions taken from bottom of the battery to the highest point on the battery. Heights may vary depending on type of terminal.
 Terminal images are representative only.
 N/A = NX available. For more information on the Single-Point Watering Kit (SPWK), please contact your Trojan Battery representative.
 Trojan's battery testing procedures adhere to both BCI and IEC test standards.

# **Terminal Configurations**



1 ELPT Embedded Low Profile Terminal



6 DT Automotive

Post & Stud

Terminal



2 EHPT



7 UT Universal Terminal



4 **EUT** Embedded Universal Terminal



10 DWNT Dual Wingnut Terminal



L-Terminal



11 ST Stud Terminal



Embedded Automotive Post Terminal

9 WNT

Wingnut

Terminal



## Experience The Trojan Difference – Reputation Built on Quality, Leadership and Innovation

#### Leadership

Founded in 1925 by co-founders George Godber and Carl Speer, Trojan Battery Company is the world's leading manufacturer of deep-cycle batteries. From deep-cycle flooded batteries to deep-cycle AGM and gel batteries, Trojan has shaped the world of deep-cycle battery technology with over 85 years of battery manufacturing experience. With the invention of the golf car battery for the Autoette vehicle in 1952, Trojan pioneered the development of deep-cycle battery technology for the golf industry; successfully introducing mobilization to the game of golf. For Trojan, this began a legacy of leadership and innovation that prevails today in the global, deep-cycle markets spanning applications for marine and recreational vehicles, aerial work platforms, transportation, renewable energy, golf, and floor machines. Today, Trojan batteries are available worldwide through our global network of master distributors.

Headquartered in Santa Fe Springs, CA, Trojan's operations include ISO 9001:2008 certified manufacturing plants in California and Georgia, two advanced research and development centers dedicated exclusively to deep-cycle battery technologies and international offices located in Europe, UAE and Asia. Trojan is a proud member of the Battery Council International (BCI) and a technical research partner with the Bulgarian Academy of Sciences.

#### Research and Development

Quality and innovation are the cornerstones of our product development. Engineering teams, backed by over 200 years of deep-cycle development expertise, work together to innovate and bring to market advanced battery technologies that exceed our customers' expectations for outstanding battery performance.

To ensure the quality and superior performance of our batteries, Trojan applies the most rigorous testing procedures in the industry to test for cycle life, capacity, charger algorithms and both physical and mechanical



Prototype development and evaluation

integrity. Trojan's battery testing procedures adhere to both BCI and IEC test standards. Trojan's state-of-the-art R&D facilities include charger characterization and analytical labs, battery prototype and evaluation labs and battery autopsy centers all dedicated to providing you with a superior battery that you can rely on.

#### **Environmental Stewardship**

At Trojan Battery, when we say, "Clean energy for life<sup>TM</sup>," we mean every word. As proactive supporters of environmental sustainability, our environmental stewardship focuses on clean energy initiatives and recycling programs.

- Trojan batteries are 97% recyclable. The container plastic, battery lead and electrolyte from old deep-cycle batteries can be
  recycled to produce new Deep-Cycle batteries.
- Through its partnership with Southern California Edison (SCE) Trojan saves over 8 million kilowatt hours and cuts CO2 emissions by over 12 million pounds significantly reducing our annual energy consumption and carbon foot print.



TROJAN BATTERY COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV =ISO 9001:2008 =



### Your Local Trojan Battery Representative:

For more information, call 800.423.6569 or + 1.562.236.3000 or visit www.trojanbattery.com



© 2014 Trojan Battery Company. All rights reserved. Trojan Battery Company is not liable for damages that may result from any information provided in or omitted from this publication, under any circumstances. Trojan Battery Company reserves the right to make adjustments to this publication at any time, without notices or obligation. Please check the Trojan Battery website (www.trojanbattery.com) for the most up-to-date information.